

Specifications

Environment	Line level unbalanced analogue audio
Devices	DVD players, satellite receivers, MPEG players, laptops, hi-fidelity stereo audio amplifiers, audio switchers, AV monitors and other line level audio equipment.
Transmission	Transparent to the user
3 dB Bandwidth	20 Hz to 20 kHz over the distance range
Maximum Input	1.1 Vp-p
Insertion Loss per Balun Pair	Less than 2 dB over the frequency range
Common Mode Rejection Ratio (CMRR)	Greater than 60 dB at 1 kHz Greater than 40 dB over the frequency range
THD	Less than 0.007% at 1 kHz
Audio Source Impedance	100 ohm maximum
Audio Receiver Impedance	10 kohm minimum
Max. Distance via Cat 5E/6 UTP/STP Cable	3,250 ft (1 km)
Pin Configuration (RJ45)	Audio 1 (White): Pins 1(R) & 2(T) Audio 2 (Red): Pins 3(R) & 6()
Cable: Cat 5E/6 UTP/STP	24 AWG or lower solid copper twisted pair wire Impedance: 100 ohm at 1 MHz Maximum capacitance: 20 pf/ft Attenuation: 6.6 dB/1,000 ft at 1 MHz
Cable: Coax	Shielded audio cable
Connectors	Two (2) RCA-M 6" cable leads One (1) RJ45
Temperature	Operating: 0° to 55°C Storage: -20° to 85°C Humidity: Up to 95% non-condensing
Enclosure	ABS. Fire retardant plastic
Dimensions	2.40" x 2.25" x 1.00" plus 6" audio lead
Weight	3.1 oz (89 g)
Warranty	Lifetime
Order Information	500028 Stereo Hi-Fi Balun



Stereo Hi-Fi Balun 500028

Quick Installation Guide

Overview

The Stereo Hi-Fi Balun (500028) allows unbalanced line level stereo audio to be transmitted up to 5,000 ft (1.5 km) via an unshielded copper twisted pair (UTP) cable in a point-to-point connection. Used in pairs, the product is designed for high fidelity applications where full audio bandwidth (20 Hz to 20 kHz) is required. Used in pairs, the Stereo Hi-Fi Balun eliminates costly and bulky audio cables, allowing audio equipment to be connected or moved within a structured cabling environment. Applications include: Audio distribution, high-fidelity sound systems, and custom residential audio systems.

MuxLab

8495 Dalton Road, Mount Royal, Quebec, Canada. H4T 1V5

Tel: (514) 905-0588 Fax: (514) 905-0589


Toll Free (North America): (877) 689-5228

E-mail: videoease@muxlab.com URL: www.muxlab.com

Installation


To install the Stereo Hi-Fi Baluns, perform the following steps:

1. One pair of Stereo Hi-Fi Baluns is required for each stereo channel.
2. Identify the pin configuration of the baluns. Two (2) twisted pairs are required as shown in the following diagram.



Note: The Stereo Hi-Fi Balun is phase polarity sensitive. Therefore, in order to achieve full stereo audio quality, please ensure that the wiring is straight-through and according to EIA568 (A or B) standard.

3. Verify the colors of the RCA plugs and connect one (1) Stereo Hi-Fi Balun to the left-audio and right-audio RCA connectors of the audio source.
4. Verify the colors of the RCA plugs and connect a second Stereo Hi-Fi Balun to the left-audio and right-audio RCA connectors of the audio receiver at the remote end.
5. Complete the connection between the two (2) baluns, using standard UTP cable, connector blocks and appropriate modular RJ45 outlets.
6. Power-on the audio equipment and check the audio quality. The audio should be clear within the maximum specified distances. The following diagram shows a typical configuration.



Troubleshooting

The following table describes some of the symptoms, probable causes and possible solutions in respect to the installation of the Stereo Hi-Fi Balun:

Symptom	Probable Cause	Possible Solutions
Poor audio quality	EMI interference	Check that wiring is not too close to transformers and ballasts.
	Split pair	Ensure that the UTP pairs are not split and that each pair of wires is twisted.
No audio	No power	Check your audio system for power.
	Open circuit	Check wiring to ensure continuity
	Defective balun	Change Stereo Hi-Fi Baluns for another pair.
Audio phase cancellation	Reversed wires	Check for straight-through wiring.
Audio weak	Distance specifications exceeded	Check DC loop resistance and verify if distance spec is exceeded. Reduce cable length or eliminate high-loss components.

If you still cannot diagnose the problem, please call MuxLab Customer Technical Support at 877-689-5228 (toll-free in North America) or 514-905-0588 (International).